



MECHANICAL POKERS & DRIVE UNITS



Engine Protection

The robust frame with side covers protects the rubber-mounted engine from external forces.

Easy to Service

Engine is easy to service with simple access to all the service points

Low Fuel Consumption

The built-in fuel tank provides hours of uninterrupted work.

Efficient & Durable





Specs	RD36	RD37D
Operating mass	28 kg	59 kg
Manufacturer/Model	Honda Engine GX160	Greaves 1520
Type	Petrol	Diesel
Power	3.6kW @ 3,600 rpm	3.67kW @ 3,600 rpm
Fuel tank capacity	3.1 Liters	4.1 Liters

Specs	RD22E
Operating mass	28 kg
Manufacturer/Model	Branded
Type	Electrical single phase
Power	2.2kW @ 2,800 rpm
Voltage	230 V, AC

REDLINE Pokers with 30mm, 45mm and 60mm Tube Head Diameter

Specs	RP30	RP45	RP60
Centrifugal force, kN	4.5	4.5	5.8
Poker Type	Pendulum	Pendulum	Pendulum
Noise Level, dB	80 - 85	78	83
Frequency, vpm	12500	12000	11300
Tube Head Diameter, mm	30	45	60
Hose Length, m	5	5	5
Weight, kg	14.5	16	18

